



**Nice SpA**  
 Via Pezza Alta, 13 Z.I. Rustignè  
 I-31046 Oderzo TV Italia  
 Phone +39.0422.853838  
 Fax +39.0422.853585  
 P.IVA 03099360269  
 info@niceforyou.com  
 www.niceforyou.com



## **ERRATA CORRIGE**

### **SPIN22KCE**

**Table No. 1: Description of the SPIN components**

Model:	Gearmotor	Guide	Radio receiver	Radio Transmitter
SPIN20KCE	SN6021	3x1m	SMXI	FLO2R-S
SPIN21KCE	SN6021	3m	SMXI	FLO2R-S
SPIN22KCE	SN6021	3m+1m	SMXI	FLO2R-S
SPIN30	SN6031	3x1m	--	--
SPIN40	SN6041	3x1m	--	--
SN6031	SN6031	--	--	--
SN6041	SN6041	--	--	--

**Table No. 3: SPIN gearmotor operative limits**

Model:	SECTIONAL door		OVERHEAD door, non-protruding (with accessory SPA5)		OVERHEAD door, protruding (with accessory SPA5)	
	Height	Width	Height	Width	Height	Width
SPIN20KCE	2.5m	3.5m	2.2m	3m	2.8m	3m
SPIN21KCE	2.5m	3.5m	2.2m	3m	2.8m	3m
SPIN22KCE	3.5m	3.5m	3.2m	2.5m	3.5m	2.5m
SPIN30	2.5m	3.5m	2.2m	3m	2.8m	3m
SPIN40	2.5m	5m	2.2m	4m	2.8m	4m
SN6031 (SNA5)	2.5m	3.5m	2.2m	3m	2.8m	3m
SN6031 (SNA6)	3.5m	3.5m	3.2m	3m	3.5m	3m
SN6041 (SNA6)	3.5m	5m	3.2m	3m	3.5m	3m

**Guide technical characteristics**

Model	Guide in SPIN20KCE and SPIN30	Guide in SPIN22KCE	Guide in SPIN40	SNA5	SNA6
Type	3-piece profile in galvanised steel	2-piece profile in galvanised steel	3-piece profile in galvanised steel	single profile in galvanised steel	2-piece profile in galvanised steel
Guide length	3.15m	4.15m	3.15m	3.15m	4.15m
Guide height	35mm	35mm	35mm	35mm	35mm
Useful stroke	2.5m	3.5m	2.5m	2.5m	3.5m
Belt width	6m	8m	6m	6m	8m
Belt Height	6mm	10mm	10mm	6mm	10mm
Resistance to traction	730N	1220N	1220N	730N	1220N